§471.36

(ee) Electrocoating rinse.

SUBPART C-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of nickel-cobalt electrocoated	
Chromium	1.25 1.86 201	0.506 0.125 89.0

(ff) Miscellaneous wastewater sources.

SUBPART C-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of nickel-cobalt formed	
Chromium	0.091 0.136 14.7	0.037 0.091 6.50

[50 FR 34270, Aug. 23, 1985; 51 FR 2886, Jan. 22, 1986, as amended at 54 FR 11350, Mar. 17, 1989]

§ 471.36 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

Subpart D—Precious Metals Forming Subcategory

§ 471.40 Applicability; description of the precious metals forming subcategory.

This subpart applies to discharges of pollutants to waters of the United States, and introductions of pollutants into publicly owned treatment works from the process operations of the precious metals forming subcategory.

§ 471.41 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations for the process operations rep-

resenting the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

- (a) Rolling spent neat oils—Subpart D—BPT. There shall be no discharge of process wastewater pollutants.
 - (b) Rolling spent emulsions.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average	
	mg/off-kg (pounds per million off-pounds) of precious metals rolled with emul- sions		
Chromium	0.026	0.012	
Copper	0.147	0.077	
Cyanide	0.023	0.010	
Silver	0.032	0.013	
Oil and grease	1.54	0.925	
TSS	3.16	1.51	
pH	(1)	(1)	

¹ Within the range of 7.5 to 10.0 at all times.

(c) Drawing spent neat oils—Subpart D—BPT. There shall be no discharge of process wastewater pollutants.

(d) Drawing spent emulsions.

SUBPART D-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals drawn with emul- sions	
Cadmium	0.016	0.007
Copper	0.091	0.048
Cyanide	0.014	0.006
Silver	0.020	0.008
Oil and grease	0.950	0.570
TSS	1.95	0.926
pH	(1)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(e) Drawing spent soap solutions.